

## GPS, Acceleration & Temperature



### PRODUCT DESCRIPTION

IOTSU® L2R L03 is a wireless device that measures GPS location data combined with acceleration. IOTSU® L2R L03 is designed for tracking assets, monitoring critical transportations and cold chains, and optimizing machine and vehicle maintenance.

In addition to location tracking IOTSU® L2R L03 can measure temperature, tilt and shock. The device can also be remotely configured with wide array of downlink commands to help make the device fit various different use cases. Example parameters that can be adjusted include temperature, tilt and shock thresholds, which trigger the device to send an alarm message when exceeded.

IOTSU® L2R L03 can be mounted on any object such as a deliverable package, container or vehicle. The device is maintenance-free and encased in an industrial quality casing resistant to dust and splatter. Installation is fast and easy.

IOTSU® L2R uses the global LoRaWAN network connection. There is no need for external power supply.



### TECHNICAL SPECIFICATIONS

**DIMENSIONS (LxWxH):** 140 x 60 x 40 mm

**WEIGHT:** 225g with battery

**SENSORS:** GPS, Acceleration, Temperature

**TRANSMISSION CYCLE:** Configurable, alerts

**CONNECTIVITY:** LoRaWAN

**IP CLASS:** 67

**BATTERY:** 2x size C 3.6V, replaceable.

**OPERATING TEMPERATURE:** -30°C to +50°C

**MOUNTING:** Adhesive tape, Screws

Rev 1.0\_13<sup>th</sup>Oct 2020